

**Distributed by: BOAT LIFT WORLD
877-790-LIFT**

Customer Information & Maintenance Log

Purchased From _____

Hoist # _____

Date Installed _____

Cable inspection-check for frayed or broken cables. If unsure of age of cables, or frayed or rusted--replace with new cables. Lubricate with cable lube. If boat stored over winter, inspect cables thoroughly.

How to grease your hoist--remove boat from lift.

The gear unit has 3 grease fittings. 2 of which are located on the bearing blocks and the 3rd is located on the large or, bull gear. Grease all as needed.

Apply grease to the bull gear also. Operate the hoist (while unloaded) to distribute grease on all parts.

Visual inspection of gears is recommended.

CABLE INSPECTION DATES/GREASE DATES

BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____

**Distributed by: BOAT LIFT WORLD
877-790-LIFT**

Customer Information & Maintenance Log

Purchased From _____

Hoist # _____

Date Installed _____

Cable inspection-check for frayed or broken cables. If unsure of age of cables, or frayed or rusted--replace with new cables. Lubricate with cable lube. If boat stored over winter, inspect cables thoroughly.

How to grease your hoist--remove boat from lift.

The gear unit has 3 grease fittings. 2 of which are located on the bearing blocks and the 3rd is located on the large or, bull gear. Grease all as needed.

Apply grease to the bull gear also. Operate the hoist (while unloaded) to distribute grease on all parts.

Visual inspection of gears is recommended.

CABLE INSPECTION DATES/GREASE DATES

BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____

**Distributed by: BOAT LIFT WORLD
877-790-LIFT**

Customer Information & Maintenance Log

Purchased From _____

Hoist # _____

Date Installed _____

Cable inspection-check for frayed or broken cables. If unsure of age of cables, or frayed or rusted--replace with new cables. Lubricate with cable lube. If boat stored over winter, inspect cables thoroughly.

How to grease your hoist--remove boat from lift.

The gear unit has 3 grease fittings. 2 of which are located on the bearing blocks and the 3rd is located on the large or, bull gear. Grease all as needed.

Apply grease to the bull gear also. Operate the hoist (while unloaded) to distribute grease on all parts.

Visual inspection of gears is recommended.

CABLE INSPECTION DATES/GREASE DATES

BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____
BY _____